

Specificação:

Método de impressão	Térmica direta
Densidade de impressão	384dots / linha (203DPI)
Tamanho dos caracteres	384dots / linhas, caracteres ANK, Font: A: 12 * 24dots, 1.5 (W) * 3.0 (H) mm Simplificado / Tradicional: 24 * 24dots, 3.0 (W) * 3.0 (H) mm
Tipo de código de barras	JAN13(EAN13)JAN8(EAN8)CODE39
Impressão de Comando	Compatível com & nbsp; EPSON ESC / POS
Idioma	OEM437 / Katakana / OEM850 / OEM860 / OEM863 / OEM865 / Europa Ocidental / grego / hebraico / Leste / Irã / WPC1252 / OEM866 / OEM852 / OEM858 / IranII / Letônia / & nbsp; árabe / PT151,1251 / OEM747 / WPC1257 / Vietnam / OEM864 / hebraico / WPC1255 / Thai
Velocidade de impressão	90 milímetros / seg
Largura do papel	57,5 ± 0,5 milímetros
Espessura do papel	0.06-0.08mm
MCBF (vida)	50 km
Dimensão	190 * 132 * 119 milímetros
Peso bruto	1.2KG
Cortador automático	cortador manual
Sensor	Papel Near End Sensor, Papel Sensor Fim, sensor de abertura da tampa
Rolo de Papel	Φ75mm
Interface	RS-232C, Paralela, USB, LAN
Motorista	Win 9X, Win 2000, Win 2003, Win XP, Win Vista, Win 7 & nbsp; & nbsp; compatível com ESPON
Fornecimento Printer	DC12V / 3A
Gaveta Controle de Caixa	DC12V / 1A
Temperatura de trabalho	0-45°C, Umidade: 10-80%
Salvando Temperatura	-10-60°C, Umidade: 10-90%



**58mm Thermal
Receipt Printer**

OCPP-586



Product Picture





Features

Simple but not easy

Small size and elegant design





Can drive cash drawer



Compatible with ESPON



High printing speed



Printing head life: 50KM



All-round show





Application Area

Food delivery, restaurant, Traffic Citation,
Logistics, Transportation, Warehouse management,
Delivery, Illegal Parking Ticket, Drugstore,
Price Tag, Retail/Farm



Parameter

Printing Method	Direct thermal
Print Density	384dots/line (203DPI)
Character Size	384dots/line, ANK character, Font: A: 12*24dots, 1.5(W)*3.0(H) mm Simplified/Traditional: 24*24dots, 3.0(W)*3.0(H)mm
Barcode Type	JAN13 (EAN13) JAN8 (EAN8) CODE39
Printing Command	Compatible with EPSON ESC/POS
Language	OEM437/Katakana/OEM850/OEM860/OEM863/OEM865/West Europe/ Greek/Hebrew/East Europe/Iran/WPC1252/OEM866/OEM852/ OEM858/IranII/Latvian/ Arabic/PT151,1251/OEM747/ WPC1257/Vietnam/OEM864/Hebrew/WPC1255/Thai
Printing Speed	90mm/sec
Paper Width	57.5±0.5mm
Paper Thickness	0.06-0.08mm
MCBF(life)	50km
Dimension	190*132*119mm
Gross Weight	1.2KG
Auto Cutter	manual cutter
Sensor	Paper Near End Sensor, Paper End Sensor, Cover open sensor
Roll Paper	Φ75mm
Interface	RS-232C, Parallel, USB, LAN

Driver	win 9X, win 2000, win 2003, win XP, win vista, win 7 compatible with ESPON
Printer Supply	DC12V/3A
Cash Drawer Control	DC12V/1A
Working Temperature	0-45°C, Humidity: 10-80%
Saving Temperature	-10-60°C, Humidity: 10-90%

Paper Roll Installation



- A Open the printer cover.
- B Install the roller in the roll paper, and put them into the printer.
- C Pull out some paper outside the printer and then close the printer cover.
- D Close the top cover. Press the printer cover to avoid error position of roll paper.
- E Tear-off the paper correctly.

Connection



- a. Plug the DC cord connector into the printer's power connector..
- b. Plug the data cable connector into the printer's interface connector.
- c. Plug the drawer cable into the drawer kick-out connector on the back of the printer next to the interface connector.

Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on

3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.



We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: www.ocominc.com, Together we quest for the best.

