

# Портативный лазерный сканер штрих-кода Auto Sense с подставкой (OCBS-LA09)

## Спецификация:

Технические характеристики	
Источник света:	650 нм видно
Скорость сканирования:	200 сканов в секунду
ЦПУ	32-битный
Расстояние чтения	2,5 ~ 600 мм (100% UPC / EAN)
Ширина сканирования	50mm @ 60mm, 220mm @ 200mm
Тип сканера:	Двунаправленный
Режим работы	Авточувствительность
Разрешение:	Серия 3mil с высоким разрешением / серия длиной глубины 5mil
Минимальный контраст печати:	30%, минимальная отражательная разница
Возможность декодирования:	UPC / EAN, UPC / EAN с дополнительными данными, UCC / EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, код 11, варианты RSS, китайский 2 из 5, MSI / Plessey, Великобритания / Plessey, UCC / EAN 128, китайский код, серия GS1 DataBar (RSS)
Угол сканирования	± 65 ° (наклон); ± 60 ° (шаг); ± 42 ° (рыскания)
Физические характеристики	
Поддерживаемые интерфейсы:	PS2, RS232, USB для опции
Напряжение:	5 В постоянного тока ± 5%
Текущий:	85 мА (рабочий); 100 (Макс.)
Индикатор	Веепер, LED
материал	ABS + PC
стенд	С
Габаритные размеры:	156 * 68 * 83 мм (L * W * H)
Вес:	235г
Цвет:	Серый или черный
Пользовательская среда	
Рабочая Температура:	0 °C ~ 45 °C
Температура хранения:	-40 °C ~ 60 °C
Влажность:	5% -90% (без конденсации)
Электростатический разряд:	Соответствует разгрузке воздуха +/- 15KV и +/- 8KV контактного разряда
Освещение окружающей среды	0 ~ 100 000 LUX
Технические характеристики:	Выдерживает несколько капель 1,5 м на бетонную поверхность
Классификация лазера	EN60825-1, класс 1

## Информация о продукте:





## Features

**Simple but not easy**

200scan/sec high scan rate and long reading distance;





Excellent decode capability;



KBW, RS232 and USB supported;



Durable construction combined with future-proofing





Competitive price for 32bit model



## || All-round show





## Parameter

Performance Characteristics	
Light Source:	650nm visible
Scan Rate:	200 scans per second
CPU	32 bit
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Width of Scan	50mm@60mm, 220mm@200mm
Scanner Type:	Bi-directional
Operation mode	Auto Sense
Resolution:	3mil high resolution series / 5mil long depth field series
Print Contrast Minimum:	30%, minimum reflective difference
Decode Capability:	UPC/EAN, UPC/EAN with Supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Codabar

	Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, chinese code , GS1 DataBar (RSS) series
Scanning Angle	±65°(tilt); ±60°(pitch); ±42°(yaw)
<b>Physical Characteristics</b>	
Interfaces Supported:	PS2, RS232, USB
Voltage:	5V DC±5%
Current:	85 mA (Operating); 100 (Max)
Indicator	Beeper, LED
Material	ABS+PC
Stand	Optional
Dimensions:	156*68*83 mm (L*W*H)
Weight:	235g
Color:	Grey and black
<b>User Environment</b>	
Operating Temperature:	0°C~45°C
Storage Temperature:	-40°C~60°C
Humidity:	5%-90% (non-condensing)
Electrostatic Discharge:	Conforms to +/-15KV air discharge and +/-8KV of contact discharge
Ambient Illumination	0 ~ 100,000 LUX
Drop Specifications:	Withstands multiple 1.5m drops to concrete surface
Laser classification	EN60825-1, class 1

## Shipping and payment

1. Air, Sea, Express(DHL, FedEx, UPS, EMS, TNT and so on)
2. EXPRESS: around 3-7 working days to arrive
3. INTERNATIONAL AIR MAIL: usually around 2-4 days to arrive, will also depend on which

3. INTERNATIONAL AIR MAIL, usually around 2-4 days to arrive, will also depend on which destination port
4. By sea: depend on which destination port
5. T/T
6. Western Union
7. Escrow
8. L/C

## Company Profile



OCOM Technologies Limited is a professional supplier specialized in POS and Auto-ID applications. Our products portfolio covers Barcode Scanner, Barcode Printer, Thermal Printer, Dot Matrix Printer, Magnetic Card Reader, Data Collector, POS Terminal, and other IOT products.

We have FCC, CE, RoHS, and other certifications. We have sell our products to West Europe, North American, Africa, Asia-Pacific and other countries.

OCOM has professional teams including marketing, R&D, quality control, production and sales service. All of the sales representatives have 3 to 10 years experience in international trading, which help us to meet the customers' needs.

OCOM have been sticking to the quality system of ISO9001:2008. We conduct strict IQC, IPQC and OQC inspection in every industrial procedure. Based on our strong capacity, the normal lead time for main products is about 3 to 7 days even for bulk order.

You can find more information of us at: [www.ocominc.com](http://www.ocominc.com),  
Together we quest for the best.

